



Unbroken Superiority

For more Information or Enquiries:

**E-mail: sales@virginelect.com
info@virginelect.com
www.virginelect.com**



USER'S MANUAL

DELTA 215

SPECIAL. (WATER PROOF). PASSIVE SPEAKER

Virgin UK Global Electronics Ltd constantly seeks ways to enhance our products' quality so as to keep & maintain the unbroken superiority of our virgin products which we have done for more than a decade. To achieve our mission, we reserve the right to change or alter any specification in this manual without prior notice.

Thanks for choosing virgin product

Manufactured By:
Virgin UK Global Electronics Ltd.
www.virginelect.com

IMPORTANT SAFETY SYMBOLS



Use only with the cart, stand, tripod, bracket, or table specified by the manufacturer, or sold with the apparatus. When a cart is used, use caution when moving the cart/apparatus combination to avoid injury from tip-over.

-
- The symbol is used to indicate that some hazardous live terminals are involved within this apparatus, even under the normal operating conditions, which may be sufficient to constitute the risk of electric shock or death.
-
- The symbol is used in the service documentation to indicate that specific component shall be replaced only by the component specified in that documentation for safety reasons.
-
- Protective grounding terminal
-
- Alternating current/voltage
-
- Hazardous live terminal

ON: Denotes the apparatus is turned on

OFF: Denotes the apparatus is turned off.

WARNING: Describes precautions that should be observed to prevent the danger of injury or death to the operator.

CAUTION: Describes precautions that should be observed to prevent danger of the apparatus.

IMPORTANT SAFETY INSTRUCTIONS

- **Read these instructions.**
- **Keep these instructions.**
- **Heed all warning.**
- **Follow all instructions.**
- **Water & Moisture**
The apparatus should be protected from moisture and rain, can not used near water, for example: near bath-tub, kitchen sink or a swimming pool, etc.
- **Heat**
The apparatus should be located away from the heat source such as radiators, stoves or other appliances that produce heat.
- **Ventilation**
Do not block areas of ventilation opening. Failure to do could result in fire. Always install accordance with the manufacturer's instructions.
- **Object and Liquid Entry**
Objects do not fall into and liquids are not spilled into the inside of the apparatus for safety.
- **Power Cord and Plug**
Protect the power cord from being walked on or pinched particularly at plugs, convenience receptacles, and the point where they exit from the apparatus.

Do not defeat the safety purpose of the polarized or grounding-type plug. A polarized plug has two blades with one wider than the other. A grounding type plug has two blades and a third grounding prong. The wide

- blade or the third prong is provided for your safety. If the provided plug does not fit into your outlet, refer to electrician for replacement.
- **Power Supply**
The apparatus should be connected to the power supply only of the type as marked on the apparatus or described in the manual. Failure to do could result in damage to the product and possibly the user.

Unplug this apparatus during lightning storms or when unused for long periods of time.
 - **Fuse**
To prevent the risk of fire and damaging the unit, please use only of the recommended fuse type as described in the manual. Before replacing the fuse, make sure the unit turned off and disconnected from the AC outlet.
 - **Electrical Connection**
Improper electrical wiring may invalidate the product warranty.
 - **Cleaning**
Clean only with a dry cloth. Do not use any solvents such as benzol or alcohol.
 - **Servicing**
Do not implement any servicing other than those means described in the manual. No user serviceable parts inside, refer all servicing to qualified service personnel only.
 - Only use accessories/attachments or parts recommended by the manufacturer.

1. Main Features:

- 1) . Dual 15inch two-way passive speaker system;
- 2) . Comprising a $\phi 44$ compression HF driver and two $\phi 75$ ferrite magnet LF units;
- 3) .Constant directivity horn, coverage reaching $90^{\circ} \times 40^{\circ}$;
- 4) . High efficiency, low distortion, cheap price but good performance;
- 5) . Power divider, imported materials and components, minimized phase shift and distortion;
- 6) . Road wheels on bottom for easy carry;
- 7) . Used for front amplification, stage monitor, fill and other purpose; widely used in applications like multifunction hall, auditorium, etc.
- 8) . Special water proof and scratch proof paint . Suitable for all weather conditions.
- 9) . Cabinet is made of High quality plywood material.

2.Key Specifications:

Model	DELTA 215
Type	dual 15inch two-way passive speaker system
Frequency Response(-10dB)	45Hz~20kHz
Sensitivity(1W@1M)	98dB±3dB
Max SPL	130dB
Rated Power	(continue) 1200W, (peak) 4200W
Nominal Impedance	4Ω
Input	2xSPEAKON
LF Unit	2x15" woofer/ $\phi 75$ mm voice coil/ 800W/ 4Ω
HF Unit	Compression driver/ $\phi 74$ mm voice coil/ 40W/ 8Ω
Dimension (WxDxH)	510*490*1215 (mm)
Net Weight	53kg
Gross Weight	59kg

